



**BERNARD[®]
CONTROLS**



//////// Invest in Confidence //////////////////////////////////////


New

Weatherproof
Quarter-turn Actuators
AQL RANGE

> AQL range

The essentials

for quarter-turn electric actuation



AQ1L - AQ3L



AQ7L

Product overview

Easy commissioning

Wiring diagram directly available inside the cover



Heavy duty design

Full aluminium enclosure protected by durable powder coating

Cable entries

Manual operation

Emergency intervention via manual hexagonal output 10mm



Flange according to ISO 5211

models delivered with standard adaptators

Mechanical position indicator as standard

Check the position of your valve at a glance



New camblock system

Easy set up of the travel limitation system with a standard screwdriver.

New mobile application BC App



> Get access to documentation and Bernard Controls Assistance

Product benefits

COMPACTNESS AND RELIABILITY FOR EXPLOSIVE ATMOSPHERE

• Compact & optimized design

- > Super compact design
- > Product architecture & torque range adapted to customers' requirements: 3 models from 15 to 70 Nm
- > Multi-voltage (AC/DC) & multi-frequency products : suitable whatever your location on the globe
- > 24VDC or 12VDC, both 2 or 3 wires available as an option
- > Short delivery time, even for voluminous project, thanks to large production capacity

• Easy to use

- > Easy commissioning for quick installation on site: pre-wired version, wiring diagram inside the cover, Quick connector (IP68) option
- > User-friendly set up of travel limitation system with a standard screwdriver. Camblock directly accessible at the front
- > Positionner option (4-20mA)
- > Manual operation via manual hexagonal output: essential for emergency intervention
- > BC APP: Bernard Controls new mobile application to get access to full documentation and Assistance

• Reliable design

- > BERNARD CONTROLS design methodology built-up on the nuclear market highly demanding requirements
- > 80+ years of continuous experience and BC inventor of the compact quarter-turn electric actuator
- > Extended lifetime: more than 200000 cycles attained during endurance tests in laboratory
- > Heavy duty design: full aluminum enclosure protected by durable powder coating, C4, IP68, large temperature scale
- > Self-locking at all speeds without any additional component
- > S4 Motor Service Duty. Up to 120 starts per hour at peak of operation
- > Electronic torque limiter for reinforced valve security
- > 100% of delivered products are tested with automatic process before delivery
- > Semi automated assembly line: enables complete electronics traceability

> AQL RANGE

Weatherproof Quarter-turn Actuators



The essentials

> Range overview

AQL

AQ1L-AQ3L-AQ7L

- 1Ph 85-260V 50/60Hz
- 24VDC 3 wires
- 12V DC - 2 or 3 wires (on request)
24V DC - 2 or 3 wires (on request)

On-Off Class A as standard

> OPTIONS

- + Position transmitter (4-20mA out)
 - + Positioner (4-20mA in/out)
> Class B
- Quick connector



Contents

Product specifications - AQL	3
Product selection	5

AQL

PRODUCT SPECIFICATIONS

GENERAL	Description	AQL actuators include a multi-voltage board to supply a 24VDC motor, compact gear case, emergency manual override and standard star-shaped output
	Torque range	15N.m to 70N.m
	Duty Classification	Adapted to process requirements: <ul style="list-style-type: none"> • On-Off: Class A actuators complying with EN15714-2 • Inching/Positioning: Class B actuators complying with EN15714-2
ENCLOSURE - PROTECTION	Casing	<ul style="list-style-type: none"> • Aluminium die casting • Cover fastened by captive and stainless steel screws
	External Protection	<ul style="list-style-type: none"> • Type : Epoxy powder coating as standard • Protection: C4 according to ISO 12944 • For colors and finishes, please consult us
	Weatherproofness	IP68 NEMA 4X as standard <i>Relative humidity: 0 to 95%.</i>
	Ambient temperature range	-20...+60°C / -4 ... +140°F Other temperatures, please consult us
MOTOR	Motor technology	DC motors
	Motor duty rating	On/Off operation (complying with EN15714-2 Class A) and Inching/Positioning (complying with EN15714-2 Class B); S4-30% motor duty rating. Up to 120 starts per hour at peak of operation. <i>(Voltage ±10%, frequency ±2%)</i>
MECHANICAL SPECIFICATIONS	Gear design	Actuator is mechanically self-locking
	Manual emergency operation	Manual emergency operation via manual hexagonal output 10mm
	Output flange	Actuator flanges comply with ISO 5211
	Lubrication	The actuators are lubricated for the product lifetime and do not require any special service.
ELECTRICAL SPECIFICATIONS	Power supply	<ul style="list-style-type: none"> • The actuators can operate on a range of single phase power supply from 85VAC to 260VAC.
	Terminal compartment	<ul style="list-style-type: none"> • Screw-type terminals for controls and power supply. Internal earth grounding post. • Quick connector (on option)
	Conduit entries	2 x M20 as standard
POSITION SENSORS	Travel limit systems	<ul style="list-style-type: none"> • Limit switches actuated by adjustable camblock • 2 SPDT switches as standard (Open and Close) + 2 auxiliary switches (for signaling); 250VAC-5A/ 48VDC-2.5A (resistive load)
	Inching/Positioning control	POSITION TRANSMITTER OPTION: 2 wires for 4-20mA

AQL

PRODUCT SPECIFICATIONS

<p>SETTINGS</p>	<p>Application for mobile device</p>	<p>BERNARD CONTROLS new mobile application is available as standard. BERNARD CONTROLS mobile interface allows the user to:</p> <ul style="list-style-type: none"> • Access to the documentation relative to the selected actuator (enter the Serial number) or scan the QR code on the nameplate of the actuator • Access to BERNARD CONTROLS contact information according to the area concerned
<p>CONFORMITY TO EC DIRECTIVES</p>	<p>Compliance with EC Directives</p>	<p>AQL actuators comply with:</p> <ul style="list-style-type: none"> • directive 2004/108/EC Electromagnetic compatibility • directive 2006/95/EC Low voltage • the following harmonised standards: EN 61000-6-4: Generic emissions standard for industrial environments; EN 61000-6-2: Generic immunity standard for industrial environments; EN 60034-1: Rotating electrical machines; EN 60529: Degrees of protection provided by enclosures (IP ratings code)

2/2

> Product selection

AQ001L DE 013 P A 0 0 0 E 0 M

Actuator Type

Voltage
FH=1Ph 85-260V 50/60Hz - 24VDC ABC (3 wires); DE=Direct Current 24VDC ABC (3 wires); DF=Direct Current 12VDC ABC (3 wires); DD=Direct current 24VDC PN (2 wires); DG=Direct current 12VDC PN (2 wires)

Operating time (sec)

Control Type
P=SWITCH Prewired

Duty & Modulating Classification
A=Class A;
B=Class B

Analog Signals Options
0=Without; 1=Position Transmitter; 2=Positioner;

LOGIC Options
0=N/A

Fieldbus Options
0=N/A

Certification
E=EC Standard
L=EC Low Temperature
C=CSA (Low Temperature)
R=EAC (Low Temperature)

Output Flange
0=Standard Flange

Connection Type
M=Metric
I=Imperial NPT
C= Quick Connector

Connection Type
M=Metric
I=Imperial NPT
C= Quick Connector

Output Flange
0=Standard Flange

Certification
E=EC Standard
L=EC Low Temperature
C=CSA (Low Temperature)
R=EAC (Low Temperature)

Fieldbus Options
0=N/A

LOGIC Options
0=N/A

Analog Signals Options
0=Without; 1=Position Transmitter; 2=Positioner;

Duty & Modulating Classification
A=Class A;
B=Class B

Control Type
P=SWITCH Prewired

Operating time (sec)

Voltage
FH=1Ph 85-260V 50/60Hz - 24VDC ABC (3 wires); DE=Direct Current 24VDC ABC (3 wires); DF=Direct Current 12VDC ABC (3 wires); DD=Direct current 24VDC PN (2 wires); DG=Direct current 12VDC PN (2 wires)



Solutions Overview



NEW RANGES OF ACTUATORS
AQ, AQL, AQXL, AT & BT



NEW MOBILE APPLICATION BC APP

The only application that allows not only to set up your actuator in a few clicks, but also to improve the reliability of your process thanks to key features and data for preventive maintenance. Compatible with our new controls: **LOGIC (v2)** & **INTELLI+® (v3)**

WEATHERPROOF RANGES

FIRST BC

The essentials

Quarter-turn AQL RANGE

- 15 to 70 Nm (direct mount)
- Type of Controls: > **Electromechanical SWITCH**
- BC Duty & Modulating Classification

On-Off **A** Inching Positioning **B**

- Environment: > IP68 / C4 (High paint protection option C5)
- > T: -20°C ...+60°C



Quarter-turn AQ RANGE

- 50 to 10,000 Nm (up to 1000 Nm direct mount) *Up to 1,000,000 Nm on request*
- Type of Controls: > **Electromechanical SWITCH** > **Smart LOGIC (v2)**
- BC Duty & Modulating Classification

On-Off **A** Inching Positioning **B** Modulating **III**

- Environment: > IP68 / C4 (High paint protection option C5)
- > T: -20°C ...+60°C (Low T° option -40°C)



Multi-turn AT RANGE

- 30 to 500 Nm (direct mount) | *Up to 32,000 Nm on request*
- 10 to 127 rpm (direct mount)
- Type of Controls: > **Electromechanical SWITCH** > **Smart LOGIC (v2)**

On-Off **A** Inching Positioning **B** Modulating **III**

- Environment: > IP68 / C4 (High paint protection option C5)
- > T: -20°C ...+60°C (Low T° option -40°C)
- Linear applications



FLEXIBLE & MODULAR

WEATHERPROOF RANGES

BC PREMIUM

The dedicated solutions

Multi-turn BT RANGE

- 30 to 500 Nm (direct mount) | *Up to 32,000 Nm on request*
- 10 to 127 rpm (direct mount) & **high speed: up to 180 rpm (direct)**
- Type of Controls: > **Smart INTELLI+® (v3)**
- Wiring: **Double-sealing as standard**

- > New terminal plate with pins for easy wiring
- > Quick Connector

Advanced BC Duty & Modulating Classification

On-Off **A+** Inching Positioning **B+** Modulating **III+**

- Environment: > IP68 / C4 (High paint protection option C5)
- > T: -20°C ...+60°C Low T° (Low T° option -40°C)
- Linear applications



FLEXIBLE & MODULAR

SPECIAL REQUESTS

Quarter-turn SQ RANGE

- 45 to 10,000 Nm (up to 800 Nm direct mount) | *Up to 1,000,000 Nm on request*
- With type of Controls: > **Smart INTELLI+® (v2)** With Fieldbus Redundant ... > SIL2
- Wiring: Double-sealing with INTELLI+

Multi-turn ST RANGE

- 60 to 2,200 Nm (direct mount) | *up to 20,000 Nm on request*
- 10 to 120 rpm (direct mount) | High speed: up to 190 rpm (direct & <300Nm)
- With type of Controls: > **Smart INTELLI+® (v2)** With Fieldbus Redundant ... > SIL2



EXPLOSIONPROOF RANGES

Quarter-turn & Multi-turn SQX & STX RANGES

- **SQX**: 80 to 800 Nm (direct) & up to 1,000,000 Nm on request
- **STX**: 25 to 2,200 Nm (direct) & up to 20,000 Nm on request
- Compliance with international explosionproof standards: ATEX, INMETRO, IEC-Ex, EAC-Ex, NEMA 7 & 9...
- Type of Controls: > **Electromechanical SWITCH** > **Hardwired** > **Smart INTELLI+® (v2)** > **SIL2**



BC Duty & Modulating Classification

On-Off **A+** Inching Positioning **B+** Modulating **III**

- Environment: IP68 / C3 up to C5-M / T: -20°C ...+70°C (low T° option: -60°C)
- Special configurations: Corrosion protection, Fire proofing, Extreme temperatures

FAILSAFE RANGES

Quarter-turn Failsafe Actuators FQ RANGE

Fast and shock-free reliable spring-return technology during emergency operation

BC Duty & Modulating Classification

On-Off **A** Inching Positioning **B** Modulating **III**

- Environment: IP67 / C3 / T: -20°C ...+70°C (low T° option -40°C)

Failsafe Actuators FQX RANGE

- Explosionproof versions ATEX-NEMA



Quarter-turn & Linear Failsafe FSeX RANGE

The complete combination of modern electric and power of hydraulics

BC Duty & Modulating Classification

On-Off **A** Inching Positioning **B** Modulating **III**

- Environment: IP67 / C4 / T: -20°C ...+60°C
- ATEX-NEMA, SIL3



NUCLEAR RANGES



Nuclear classified Actuators

- SQN & ST & SN & SD Nuclear qualified electric actuators
- + Full range of other Qualified Solutions: Quarter-turn, Multi-turn and Linear for inside & outside containment applications; Failsafe actuators



EXPLOSIONPROOF RANGES

Quarter-turn AQXL RANGE

- 40 Nm and 70 Nm
- Compliance with international explosionproof standards: ATEX, IEC-Ex, NEMA 7...
- Type of Controls: > **Electromechanical SWITCH**
- BC Duty & Modulating Classification

On-Off **A** Inching Positioning **B**

- Environment: IP68 / C4 (C5 on request) / T: -20°C ...+60°C
- Linear applications



CUSTOMIZED DESIGN & PROJECTS:

At any time and anywhere on the globe, BERNARD CONTROLS teams are available for dedicated support. From the design stage to installation, commissioning, maintenance and training, our experts help you to define and implement the most appropriate solution to your specific needs thanks to our local R&D centers, test labs, calculation tools and training center.



STRONG CUSTOMER SUPPORT

NEW GENERATION OF SMART CONTROLS



NEW

LOGIC (v2)

The main functions you expect from modern integrated controls

NEW

INTELLI+® (v3)

Advanced control solution for your critical applications!

BERNARD CONTROLS GROUP

CORPORATE HEADQUARTERS

4 rue d'Arsonval - CS 70091 / 95505 Gonesse CEDEX France / Tel. : +33 (0)1 34 07 71 00 / Fax : +33 (0)1 34 07 71 01 / mail@bernardcontrols.com

CONTACT BY OPERATING AREAS

> AMERICAS

NORTH AMERICA

BERNARD CONTROLS UNITED STATES
HOUSTON

inquiry.usa@bernardcontrols.com
Tel. +1 281 578 66 66

SOUTH AMERICA

BERNARD CONTROLS LATIN AMERICA
inquiry.southamerica@bernardcontrols.com
Tel. +1 281 578 66 66

> ASIA

CHINA

BERNARD CONTROLS CHINA &
BERNARD CONTROLS CHINA NUCLEAR
BEIJING

inquiry.china@bernardcontrols.com
Tel. +86 (0) 10 6789 2861

KOREA

BERNARD CONTROLS KOREA
SEOUL

inquiry.korea@bernardcontrols.com
Tel. +82 (0)2 2183 6226

SINGAPORE

BERNARD CONTROLS SINGAPORE
SINGAPORE

inquiry.singapore@bernardcontrols.com
Tel. +65 65 654 227

> EUROPE

BELGIUM

BERNARD CONTROLS BENELUX
NIVELLES (BRUSSELS)

inquiry.belgium@bernardcontrols.com
inquiry.holland@bernardcontrols.com
Tel. +32 (0)2 343 41 22

FRANCE

BERNARD CONTROLS FRANCE &
BERNARD CONTROLS NUCLEAR FRANCE
GONESSE (PARIS)

inquiry.france@bernardcontrols.com
Tel. +33 (0)1 34 07 71 00

GERMANY

BERNARD CONTROLS DEUFRA
TROISDORF (KÖLN)

inquiry.germany@bernardcontrols.com
Tel. +49 2241 9834 0

ITALY

BERNARD CONTROLS ITALIA
RHO (MILANO)

inquiry.italy@bernardcontrols.com
Tel. +39 02 931 85 233

RUSSIA

BERNARD CONTROLS RUSSIA

inquiry.russia@bernardcontrols.com
Tel. +33 (0)1 34 07 71 00

SPAIN

BERNARD CONTROLS SPAIN
MADRID

inquiry.spain@bernardcontrols.com
Tel. +34 91 30 41 139

UNITED KINGDOM

BERNARD CONTROLS UNITED KINGDOM

inquiry.uk@bernardcontrols.com
Tel. +44 (0)7435 266310

> INDIA, MIDDLE EAST & AFRICA

AFRICA

BERNARD CONTROLS AFRICA
ABIDJAN - IVORY COAST

inquiry.africa@bernardcontrols.com
Tel. +225 21 34 07 82

INDIA

BERNARD CONTROLS INDIA

inquiry.india@bernardcontrols.com
Tel. +971 4 880 0660

MIDDLE-EAST

BERNARD CONTROLS MIDDLE-EAST
DUBAI - U.A.E.

inquiry.middleeast@bernardcontrols.com
Tel. +971 4 880 0660

More than 50 agents and distributors worldwide. Contact details on www.bernardcontrols.com

BROCHURE_AOL_ETIC_GRP_rev01D
This document and the contents here of are proprietary to Bernard Controls. It can be amended
and changed without prior notice. Any unauthorized reproduction is strictly prohibited.